

CE7-12 ▶ 12V 7 AH

SMF VRLA RECHARGEABLE BATTERY



APPLICATIONS

- ✓ UPS Systems
- ✓ Central Battery Systems
- ✓ Emergency Lighting
- ✓ Fire Alarm System
- ✓ Security Systems
- ✓ Elevators
- ✓ Hospital & Laboratories
- ✓ Banks, Finance & Data Centers

COMPLIANCE

- ✓ IEC 60896 – 21
- ✓ IEC 60896 – 22
- ✓ IEC 61427 – 1:2013

QUALITY STANDARDS

Manufactured in best-in-class facility certified to

- ✓ ISO 9001: 2015
- ✓ ISO 14001: 2015
- ✓ OHSAS 45001: 2018

TECHNICAL FEATURES

- ✓ Non-Spillable Sealed Construction
- ✓ Sealed Lead Acid Battery
- ✓ AGM, ABS, Gas Recombination
- ✓ Venting System for low internal pressure
- ✓ Low Self-Discharge & High-Power Output
- ✓ Heavy-Duty, Highly Optimized Grids
- ✓ Maintenance-Free Operation

CHARACTERISTICS


Nominal Voltage	12 V	
Capacity 25°C (77°F)	20 Hour rate	7Ah
	10 Hour rate	6.5Ah
	1 Hour rate	4.2Ah
Internal Resistance (25°C, 100%Charge)	Approx.25m Ω	
Self-Discharge (25°C)	3 Months	Remaining Capacity 91%
	6 Months	Remaining Capacity 82%
Operating Temperature	Discharge	-15°C to 50°C
	Charge	-10°C to 50°C
	Storage	-20°C to 50°C
Nominal Operating Temperature	≤ 25°C (77°F)	
Maximum Discharge current	105A (5sec)	
Maximum Charging current	2.1A	
Charge Methods Constant Voltage Charge 77°F (25°C) - Standby Use	13.50 to 13.80 V	
	Temp. Compensation -18mV/°C	
Charge methods Constant Voltage Charge 77°F (25°C) - Cycle use	14.40 to 14.80V	
	Temp. Compensation -30mV/°C	
Design Life	5 Years	

CONSTANT CURRENT DISCHARGE (Amperes) AT 25°C

End Cell Voltage (ECV)	DURATION								
	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	26.8	16.9	13.2	7.46	4.59	1.74	1.22	0.66	0.36
1.65	25.9	16.4	12.9	7.31	4.52	1.72	1.21	0.66	0.35
1.70	24.9	15.8	12.4	7.08	4.40	1.71	1.21	0.66	0.35
1.75	23.9	15.1	12	6.91	4.31	1.70	1.20	0.65	0.35
1.80	22.5	14.2	11.4	6.66	4.18	1.65	1.16	0.64	0.34

CONSTANT POWER DISCHARGE (Watts) AT 25°C

End Cell Voltage (ECV)	DURATION								
	5min	10min	15min	30min	1h	3h	5h	10h	20h
1.60	49.8	31.9	25.1	14.1	8.86	3.42	2.44	1.32	0.71
1.65	48.3	30.7	24.4	14.0	8.73	3.41	2.43	1.31	0.71
1.70	46.2	29.6	23.6	13.4	8.51	3.37	2.41	1.30	0.71
1.75	44.2	28.2	22.7	13.1	8.33	3.36	2.37	1.30	0.70
1.80	41.9	26.7	21.6	12.6	8.06	3.26	2.33	1.27	0.69




DIMENSION


Length	Width	Height	Total Height	Weight (kg)
151 mm	65 mm	94 mm	100 mm	2.20 kg




Float life vs Temperature




Charging Characteristics (25°C)




Recommended charging voltage vs temperature




Self-discharge Characteristics



Cycle life vs D.O.D (25°C)



Open Circuit Voltage (V) vs Capacity (25°C)



**Standards, Specifications and design are subject to change without notice.